

# MS-15/30



## CEILING SPEAKER



### FEATURES

- **VERSATILE MODELS**  
The ceiling speakers are designed with steel ABS resin.
- **EASY INSTALLATION**  
You can install easily by using provided spring and steel cover.
- **EFFICIENCY FOR P.A SYSTEM**  
Marching transformer is incorporation for high efficiency of P.A use.
- **2 WAY SYSTEM**  
These speakers are designed coaxial type unit.  
Sound is clear and smooth.

### SPECIFICATIONS

- **ELECTRICAL** \* 0dB=0.775Vrms
  - MS-15
    - Rated Input .....15W
    - Impedance ..... 660Ω, 1kΩ, 2kΩ
    - Frequency Response .....250Hz-17kHz
    - SPL(1m/1W) .....97dB
  - MS-30
    - Rated Input .....30W
    - Impedance ..... 330Ω, 500Ω, 1kΩ
    - Frequency Response .....220Hz-18kHz
    - SPL(1m/1W) .....97dB
    - Material of Case .....Aluminum
    - Body .....ABS RESIN
    - Cover .....PAINTED STEEL
- **GENERAL**
  - Weight .....MS-15: 2.5kg  
MS-30: 3.5kg
  - Dimensions .....220(W) × 286(H) × 139(D)mm

MS-15/30 TERMINAL CONNECTION

---

